
# **3-part Aluminium Lifting Column**

### MAC5U

Up to 3500N





### 3-part Aluminium Lifting Column MAC5U

Low built-in measurement, long stroke. For industrial/medical use.

MAC5U is a completely new developed lifting column, designed to meet the requirements of aesthetics and quality in industrial workplaces. Usable in many industrial/medical applications. In the development, high stability and a reasonable price level were emphasized. MAC5U is a Low-Noise lifting column. The lifting column is designed for loads of max. 3500N and can be moved up to 47mm/s without load. The bending moment is 1000Nm. Plug & Play: You can also get MAC5U as a complete Plug & Play solution, including one or more MAC5U lifting columns, a Movetec control box 230V AC, all cables and a control panel.

Option: By Selecting a control box with Bluetooth®, MAC5U are easily controlled by iPhone® or Android®-Smartphone.

#### Material specifications:

Outer profile: Anodized Aluminium Middle profile: Anodized Aluminium Inner profile: Anodized Aluminium Friction sliders: POM Derivate Top- and Bottom plate: Steel

Lifting system drive parts: Aluminium, Steel, ABS, POM, PP

#### Technical data:

Max. load: 3500 N (depends on the stroke length)

Max. speed without load: 47mm/sek (800 N) (depends on force)

Stroke length: 200-800mm/special versions up to 1200mm (depends on force)
Dyn./static bending moment: 800/1000 Nm (depends on the stroke length)

Built-in measurement/length: 1/2 stroke length+144mm/244-744/819mm Operation temperature: +5°C-+45°C

Power supply/Voltage: 12/24V DC Cable out: Cable out in the outer profile Intermittens: 10-25% Double Hall-sensors: Yes

Top plate size: 241mm x 88mm Bottom plate size: 191mm x 61mm Outer profile size: 240mm x 87mm Inner profile size: 191mm x 61mm

Mounting track: Width top 8,1mm/inside 8,1-12mm/depth 5mm

Control box: More options, see www.movetec.dk

Synchronized drive: Max.32x/16x lifting columns in synchronized drive

Control panel: More options, see www.movetec.dk


Options: Bluetooth® controlling for iPhone®- and Android® Smartphones. Potentiometer. 12 V DC. Top- and bottom mounting plates. . Cable out in the inner profile (see MAC5). Control box with Lithium-Ion battery pack. 100% brake. Small remote control.



## 3-part Aluminium Lifting Column

### MAC5U

Up to 3500N



#### Control boxes and control panels:

MAC5U can be used with all Movetec control boxes and Movetec control panels. Some control boxes can also be programmed for customer-specific functions - please contact us with your wishes, we are looking forward to your call: +45 64 89 28 05. Movetec also offers tailor-made Plug & Play lifting column solutions.

#### **CAD-drawings:**

Gear/drive-

type

no.

G1

You can download 3D-drawings (STEP-Data) for MAC5U for your CAD-Program or as a PDF-file on our homepage.

Load,

Pull

Ν

1750

#### Lifting columns data:

Load,

Push

Ν

1750

<b>Bluetooth</b>	GET IT	on ogle Play	Download on the App Store		Further info
K2	1500	1500	7,0	47	200 -1200
K1	800	800	3,5	34	200 -1200
J2	2000	2000	6,4	24	200 -1200
J1	1000	1000	3,2	47	200 -1200
G2	3500	3500	9,4	34	200 -1200

Typ. power con-

sumption by load

Α

4,7

Bluetooth® is a registered trademark and are the proporty of the owner Bluetooth SIG, Inc. Android®/ Google Play® is registered trademarks and are the proporty of the owner Google Inc. Apple®/ App Store® is registered trademarks and are the proporty of the owner Apple Inc. Other trademarks and trade names are the proporty of their respective owners.

## Inner profile bottom plate 178 191 Outer profile 228 241 Profile 159 240 All measures in mm Socket Plug 8765 <del>元日上</del> 5678 1234

#### Manuals, installation instructions, approvals/certificates, Safety instructions etc.:

Motor+

Hall 2

Installation manuals, assembly- and installation instructions, warnings, instructional videos and further information, can be found on our homepage: www.movetec.dk

Built-in measurement

#### ding moment without load (by stroke length mm 200-1200mm) in mm Nm 200 -1200 244 - 744/819 800/1000 244 - 744/819 800/1000 244 - 744/819 800/1000 244 - 744/819 800/1000

244 - 744/819

244 - 744/819





Stroke length

Molex plugs/connections:

Product

Color

Dual Hall









ŲŲ



Max. static ben-

800/1000

800/1000



© Copyright Movetec Solutions ApS. LKD/MAC5U/dat191-UK/3/100/1121



Speed,

mm/s

24

Tel. +45 64 89 28 05 · www.movetec.dk

True Innovative Moving Technology